



Security

# 1" & 2.5"

## MAIN VAULT DOOR SERIES



PRIVACY • SECURITY • ASSET



STRENGTH




CUSTOMER SERVICE



WORLD CLASS

# SPECIFICATIONS



Ref	Specifications (mm)	1" Main Vault Door	2.5" Main Vault Door
A	Front Door Plate Thickness	25	70
B	Door Thickness	162	182
C	Minimum Wall Thickness	250	250
(D)	Wall Slot Drilling Height	2,230	2,290
E	Wall Slot Drilling Width	1,300	1,310
(F)	Door & Frame Height	2,169	2,170
G	Door & Frame Width	1,190	1,206
(H)	Door Height After Installation	2,000	2,000
I	Door Width After Installation	900	900
J	Door & Frame Width at 180° Open	2,120	2,148
K	Distance at 90° Open	1,037	1,050
L	Distance at 180° Open	237	256
M	Grille Gate Width 180° Open	2,044	2,044
N	Grille Gate Distance 90° Open	975	975
O	Grille Gate Distance 180° Open	65	71
	Moving Bolts / Bolts Diameter 38 mm	11 Sets	11 Sets
	Fixed Bolts / Bolts Diameter 38 mm	7 Sets	7 Sets
	Weight +/- 10 %	700 Kg.	693 Kg.

# QUALIFICATIONS



## SSI (Structural Steel Integration)

Crafted from reinforced thick steel and seamlessly welded, boasts a strong unified structure that is highly resistant to forced entry and nearly indestructible.



## XLarge Bolts

Equipped with 38 mm diameter bolts and rust-resistant coating, these locks strengthen the door panel and protect against prying and cutting, enhancing security.



## CS350 Barrier Material

The CS350-infused material boasts fire resistance, anti-drill strength, and extra thickness for superior protection against heat, impact, and fire.



## Multi Protection Door

The door features 162 mm or 182 mm thickness, reinforced with 25 mm or 70 mm alloy steel and fire-retardant features, combines drill resistance and reinforced hinges for enhanced security.



## S&G Combination Lock

The UL-certified S&G combination locks feature a 4-digit code with over 100 million possible combinations and include a combination ring to deter code theft.



## 8 Lever Key Lock

This lock has an 8-lever, double-bit system and comes with a durable, hard-to-copy metal key, increasing security against counterfeiting.



## Automatic Relock System

The safe has an automatic relock system with safety glass and a solid code mechanism to prevent tampering, ensuring reliable security.



## Drill Protection Alloy Steel

With a puncture-resistant steel plate made from a custom alloy, it protects the key code mechanism, keys, and all points.



## High Quality Paint

The door has been polished and treated for rust prevention before being painted in an automotive oven to ensure a long-lasting and shiny finish.

